



DVB Cine S2

Digital
Devices



- DVB-S / S2 Dual Tuner
2x HD / SD tuners
- HDTV
H.264 / MPEG4
- PCI Express
Connect via PCIe x1 up to x16 slot
- Expandable Modular System
Combine multiple DVB components
Huge expansion potential - see next page!
- Ultra Low profile
Full height bracket included
- DiSEqC 2.0
Bi-directional channel data support
- Unicable® SCR / CENELEC En50494
Up to 8 tuners via 1 antenna cable!
- greenIT 
Power consumption **only** ≈ 2 watts
- Multiple OS Support
Microsoft Windows® 7 MCE &
Linux® supported

TECHNICAL SPECIFICATIONS

Satellite features:

- Symbol rate: up to 45Msps DVB-S2
- LNB Power: +14VDC or +18VDC or without power supply (up to 500mA)
- L-band: 950 Mhz to 2150 MHz
DVB FEC: (Auto Spectral Detection)
- Modulation QPSK/8PSK
- Full DiSEqC 2.X support

Standard connections:

- PCI Express
- L-band Input connector
(supports power to the LNB)

Security:

- Designed and produced to European standards, German DIN EN ISO 9001:2000

Unicable® compliant:

- SCR / CENELEC En50494

Environmental standards:

- RoHS Conformity
- WEEE DE 99353762 (German)

Power consumption:

- PCIe compliant
- 1.8 Amps max. via 12V LNB power
- ≈ 2 watts without LNB power

System requirements:

- Dual Core Intel® or AMD® CPU
- 512 MB RAM
- 1 free PCIe slot
(x1 up to x16)

Supported operating systems:

- Linux® (Kernel 2.6.34)
- Microsoft Windows Vista®
- Microsoft Windows 7 **32 and 64 Bit**
(incl Windows® Media Center)

Dimensions:

H 2,165 inches
L 6,181 inches
D 0,551 inches


MADE in GERMANY



DVB Cine S2

Digital
Devices

*Unlimited flexibility and
expandability...*



**HDTV
on your PC**

optional accessories


Common Interface (CI) with MTD Technology

The CI is compatible with all
Digital Devices DVB cards
(see the example below)



DuoFlex DVB-S2 Dual Tuner

Add a DuoFlex S2 with 2 DVB-S2 tuners
(see the example below)



DuoFlex DVB-C/T Dual Tuner

Add a DuoFlex C/T with 2 DVB-C/T tuners
(see the example below)



The Digital Devices System

From just 1 cine S2 Dual Tuner PCIe card the system can be upgraded easily and powerfully

Dual Tuner (2 discrete tuners per card)

Simultaneously record 1 program while
watching another.

Unicable® Support

Connect up to 8 tuners via one antenna cable
with Unicable® / SCR / CENELEC En50494
compliant LNB or Multiswitch.

Support for up to 6 tuners

DVB-S2 and/or DVB-C/T in any combination

Low profile

4 tuners can be mounted on just 1 PCI bracket.
(see pictures on the right)

CI with MTD Technology (optional)

MTD (Multi Transponder Decrypting): only 1
CAM is needed to decrypt 4 encrypted TV
channels. View 1 encrypted program while
recording up to 3 others.

NB Not all CAMs support this feature.
Compatible CAMs can be found on our
website.

BIG SAVINGS!

MTD saves the extra cost of buying
multiple CI cards, CAMs and Smart
Cards. Only 1 Common Interface with 1
CAM and 1 Smart Card needed. No need
to buy multiples.


Add

1 DuoFlex S2 =
4 DVB-S2



Add

2 DuoFlex S2 =
6 DVB-S2



Add

1 or 2 CI =
2 DVB-S2 +
1 or 2 CI



Add

1 DuoFlex C/T =
2 DVB-S2 +
2 DVB-C/T



Add

1 DuoFlex C/T +
1 DuoFlex S2 =
4 DVB-S2 +
2 DVB-C/T



Add

1 DuoFlex C/T +
1 CI =
2 DVB-S2 +
2 DVB-C/T +
1 CI



For more products and expansion options, visit our website:

www.digital-devices.de



Digital Devices GmbH - www.digitaldevices.de